

Submersible Pump w/ DFC1 Standard Controller Model PVL-EC-DFC1



PVL-EC-DFC1 Features Energy Savings Pump

- 1/3HP permanent split capacitor motor with thermal overload protection
- Proven design – thousands in daily use
- Cast iron pump housing for quiet operation
- Oil filled motor housing for lifetime lubrication and rapid heat dissipation
- Commercial grade epoxy coating for corrosion and rust resistance
- Mechanical seals (nitrile parts with carbon and ceramic faces)
- Effluent rated – vortex impeller, passes limited amount of 1/2" solids
- High output; 42 gpm @ 10' tdh
- Energy Savings – uses 50% less power than most sump pumps
- CSA Certified

Dual Float Switch

- Two micro reed activated floats for added reliability
- Protective cage prevents debris from interfering with floats
- Mounts to discharge pipe with included hardware
- Easy Installation


DFC1 Standard Controller

- This control box is a piggyback switch that powers the dual float. The DFC1 Controller will activate the pump when either float is lifted, and shuts off automatically 10 seconds after the float drops

Pump Specifications

Horsepower: 1/3	RPM: 1550
Volts: 115	Full Load Amps: 5.0
Power Cord: 10'	Weight: 27.5 lbs.
Dimensions: (H x L x W in.):	11.08" x 8.79" x 8.48"

Performance Curve



3 Year Limited Warranty