



# JMI PUMP SYSTEMS

Your Partners in Pumping Since 1958

W194 N11695 McCormick Drive

Germantown, WI 53022

262-253-1353 • 800-234-5490

www.jmipumps.com • sales@jmipumps.com

## SUBMERSIBLE SEWAGE PUMP

### Model PVL-9S-JMI

### FEATURES

- Rated for continuous duty use in sewage and water transfer applications.
- Energy-efficient low amp draw motor with thermal overload protection.
- Heavy-duty epoxy-coated all cast iron pump.
- 2" solids handling/NPT discharge.
- Cast iron Vortex impeller.
- 20' power cord.
- Upper and lower ball bearings.
- Carbon ceramic shaft seal.
- CSA Certified.
- 3-year warranty.



### SPECIFICATIONS

HORSEPOWER	4/10
VOLTS	115
POWER CORD	20'
RPM	3600
FULL LOAD AMPS	8.5
WEIGHT	40 lbs.
DIMENSIONS (H X L X W)	10.4" x 8.8" x 13.1"

### CONSTRUCTION

IMPELLER TYPE / MATERIAL	Cast Iron Vortex
SHAFT	Stainless Steel
MOTOR	PSC Motor with Thermal Overload Protection
MECHANICAL SHAFT SEAL	Carbon Ceramic
BEARINGS	Upper and Lower, Ball Oil Lubricated
O-RINGS	Buna-N
FASTENERS	Stainless Steel
POWER CORD	SJTW



This JMI Submersible Sewage Pump ran for more than 250,000 cycles in the onsite JMI Proving Grounds. The 9S-JMI and switch still met performance specifications upon test completion.

### PERFORMANCE CURVE

